



# MOTOR OIL VX 0W-20

## Product Description:

**MOTOR OIL VX 0W-20** is a fully synthetic fuel saving long life oil based for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 508.00/509.00 has been prescribed.

**Remark: This product is not backwards compatible with older vehicles that require the VW 504 00/507 00 specification.**

**MOTOR OIL VX 0W-20** is formulated with high quality 100% Poly Alpha Olefin (PAO) base stocks in combination with an unique additive technology to achieve the following performance:

- Exceptional good low temperature properties.
- Excellent protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Improved fuel economy.

**MOTOR OIL VX 0W-20** meets the following performance criteria:

**Exceeds**                      **VW 508 00 / 509 00**                      **(VW TL 52577)**  
**Porsche C20**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-20
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	837
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	42
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	8.5
Viscosity Index		ASTM D2270	183
Viscosity CCS @-35°C, max	cP	ASTM D5293	3780
Flash Point COC	°C	ASTM D92	>205
Pour Point	°C	ASTM D7346	-54
Total Base Number	mgKOH/g	ASTM D2896	8.7
Sulphated Ash	%Wt	ASTM D874	0.8

**Product Nr:** 42170

**Date Superseded:** 05-07-2017

**Date Issued:** 10-12-2019

**Revision nr:** 02